


150 Watt HID Ballast

Ballast Code: HSJ15223221

| Electrical Data (Ballast) | |
|---------------------------|---------|
| Lamp Watts (W) | 150 |
| Lamp Current (A) | 1.8 |
| Input Voltage at 50Hz (V) | 230/240 |
| Circuit Watts (W) | 176 |
| Running Current (A) | 0.8 |
| Delta T (°C) | 75 |
| tw (°C) | 140 |
| ta (°C) | - |
| Thermal Cut-out | Y |
| Capacitor Value (µf) | 20 |
| Capacitor Voltage (V) | 250 |

Physical Data (Ballast)




| Dimensions (mm) | L | W | H |
|-----------------|---------|----|----|
| | 120 | 69 | 56 |
| Fixings (mm) | 106-111 | | |
| Weight (kg) | 1.8 | | |

Standard Ignitor 220/240V ±10% 50/60Hz

Ignitor Code: PXE100255


| Electrical Data (Ignitor) | |
|----------------------------|--------------|
| Wattage (W) | 35-450 |
| Timed | N |
| Ignitor Type | Superimposed |
| Max Lamp Current (A) | 5 |
| Pulse Magnitude (kV) | 3.0-4.5 |
| Max. Lead Capacitance (pF) | 100 |
| Max Case Temp (°C) | 105 |
| Internal Temp (°C) | 30 |

Physical Data (Ignitor)




| Dimensions (mm) | L | W | H |
|-----------------|-------|----|----|
| | 71 | 33 | 31 |
| Fixing | M8x10 | | |
| Weight (kg) | 0.18 | | |

Capacitor

| | |
|----------------|-------------------------------------------------------------------------------------|
| |  |
| Value µf±10% | 20.0 |
| Product Code | 20/250 |
| Dimensions ØxL | 35x98 |

Circuit Diagram



Notes:

Data is based upon tests performed by Venture Lighting in a controlled environment and is representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.