

Description: HIT 250W/U/LU/BDX

Performance Data


Dominant Wavelength	462
% Saturation	77
Rated Life (Hrs @ 10Hr./Start)	3000
Chromaticity (CIE - X Y)	180,99
Typical Warm Up Time (Minutes)	3-5
Typical Hot Restart Time (Minutes)	8-12

Physical Data

Base Designation	E40
Bulb Designation	T46
Bulb Diameter (mm)	46
Max. Overall Length (mm)	225
Light Centre Length (mm)	146
Effective Arc Length (mm)	27
Max. Base Temperature (Å°C)	250
Max. Bulb Temperature (Å°C)	400
Socket Pulse Rating (KV)	5
Mercury Content (mg)	30

Lamp Electrical Data

Nominal Lamp Wattage (W)	250
Lamp Operating Voltage (V)	100
Lamp Operating Current (A)	3.0
Min. Open Circuit Voltage (RMS)	198
Min. Starting Pulse (Peak V)	2800-4500
Min. Pulse Width (Microseconds)	1 @2500V
Min. Pulse Rate Per Å½ cycle	1
Pulse Position (Electrical Degrees)	60-90, 240-270



Revision: 01-03-2012

See page 2 for product notes

Notes:

This Product Specification contains data about typical performance at nominal power. Actual values may depend on ballast and applications. Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives.