

# 15W LED Downlight - Pro, 830, With Driver

Order Code: DWL070

## Photometric Data

Colour Rendering Index (CRI)	80-89
Lumens	1800
LPW (lm/W)	120
Colour Temperature (K)	3000 - 3000
SDCM	<5
Light Distribution	Symmetric
Lens / Reflector	Diffuser lens/optic/panel

## Life Data



Rated Life L70/B50 @ 25°C	50000
---------------------------	-------

## Electrical Data

Input (W)	15
Input (V)±10%	220 - 240
Voltage Type	AC
Power Factor	0.9
Energy Efficiency Class (EEC)	A++, A+, A (LED)
Electrical Class	II
Type of Wiring	Ending
Wiring X-sec (mm <sup>2</sup> )	1.0
Non-dimmable	Yes

## Physical Data

Surface Protection	Powder Coating
Degree of Protection (IP)	IP40
Housing Colour	White
Housing Material	Aluminium
Reflector	None
Height/Depth (mm)	40
Diameter (mm)	225
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Cutout Height for Recess Mount (mm)	60
Cutout Diameter for Recess Mount (mm)	200
Lamp Type	LED Not Exchangeable
Surface Protection	Powder Coating
Cover Material	Opal Plastic



# 15W LED Downlight - Pro, 830, With Driver



Order Code: DWL070

## Environmental Data

Ambient Rated Temperature Range (°C)	-10 to 35
--------------------------------------	-----------

## Accessories

EMG013 - Emergency Downlight
------------------------------

EMG018 - Remote Emergency Pack
--------------------------------