

# 30W VSoldier Streetlight, D1, 740

Order Code: STL060-30-D1

## Photometric Data

Colour Rendering Index (CRI)	70-79
Lumens	3675
LPW (lm/W)	122
Colour Temperature (K)	4000 - 4000
Lens / Reflector	Refractor Lens

## Life Data


Rated Life L80/B50 @ 25°C	260000
Rated Life L90/B50 @ 25°C	114000

## Electrical Data

Input (W)	30
Input (V)±10%	220 - 240
Voltage Type	AC
Power Factor	0.95
Energy Efficiency Class (EEC)	A++, A+, A (LED)
Electrical Class	I
Type of Wiring	Ending
Wiring X-sec (mm <sup>2</sup> )	1.5
LED Nominal Current	700 - 700

## Physical Data

Surface Protection	Plastic Coated
Degree of Protection (IP)	IP66
Mounting Method	Post Top/Side Entry
Housing Colour	Grey
Housing Material	Aluminium
Length (mm)	530
Width (mm)	283
Height/Depth (mm)	115
Mounting Diameter (mm)	60 - 60
Lamp Type	LED Not Exchangeable
Surface Protection	Plastic Coated
Cover Material	Transparent Glass
Impact Strength	IK08



# 30W VSoldier Streetlight, D1, 740

---

Order Code: STL060-30-D1

## Environmental Data

Ambient Rated Temperature Range (°C)	-30 to 40
--------------------------------------	-----------

---