



CONTROLS  
AND ADVICE  
ON REQUEST



50,000  
HOURS



YEARS'  
WARRANTY



NEXT DAY  
DELIVERY

INDUSTRIAL SPECIALIST RANGE



VENTURE  
LIGHTING



A linear highbay benefitting from **optical control** designed to **optimise light distribution** while **minimising user glare**. With a high-impact resistance construction, this product is particularly suitable for sports halls. Suspension kit is supplied as standard.

# VPANEL HIGHBAY

# 81W VPanel, 850, 80X100Deg Beam, DALI

Order Code: VPL002-CD

## Photometric Data

Nominal Lumens	11250
Light Distribution	Asymmetric
Lens / Reflector	Refractor Lens

## Life Data


Rated Life L70/B50 @ 25°C	100000
Rated Life L80/B50 @ 25°C	80000

## Electrical Data

Input (W)	90
Input (V)±10%	220 - 240
Voltage Type	AC
Power Factor	0.95
Type of Wiring	Ending
Wiring X-sec (mm <sup>2</sup> )	Yes
DALI Dimming	Yes

## Physical Data

With Protective Cover	Yes
Ambient Rated Temperature Range (°C)	-40 - 40
Degree of Protection (IP)	IP20
Housing Colour	Grey
Housing Material	Aluminium
Reflector	None
Length (mm)	336
Width (mm)	307
Height/Depth (mm)	61
Lamp Type	LED Not Exchangeable
Reflector Material	Without Reflector
Impact Strength	IK08



# 81W VPanel, 850, 80X100Deg Beam, DALI

---

Order Code: VPL002-CD

## Accessories

---

ACS067 - Programming Remote for SL / SH Sensors

---

ACS030 - Commissioning Remote for SL / SH Sensors

---