

120W Vsolider Plus Streetlight, D1, 740

Order Code: STL070-120-D1

Photometric Data

Nominal Lumens	15320
Colour Rendering Index (CRI)	70-79
LPW (lm/W)	128
Lens / Reflector	Refractor Lens

Life Data

Rated Life @ 25°C (Hrs)	100000
Rated Life L90/B50 @ 25°C	72000
Rated Life L80/B50 @ 25°C	157000

Electrical Data

LED Power	109 - 109
Input (W)	119
Input (V)±10%	220 - 240
Voltage Type	AC
Power Factor	0.95
Surge Protection (kV)	10
Short Circuit Protection	Yes
Thermal Overload Protection	Yes
Electrical Class	I
Type of Wiring	Ending
Wiring X-sec (mm ²)	1.5
LED Nominal Current (mA)	2250 - 2250

Physical Data

Ambient Rated Temperature Range (°C)	-30 - 40
Degree of Protection (IP)	IP66
Mounting Method	Post Top/Side Entry
Housing Colour	Grey
Housing Material	Aluminium
Length (mm)	620
Width (mm)	350
Height/Depth (mm)	115
Mounting Diameter (mm)	60 - 60
Lamp Type	LED Not Exchangeable
Surface Protection	Plastic Coated
Cover Material	Transparent Glass
Impact Strength	IK08
Warranty (year)	12

