

90W Elite Floodlight, 840

Order Code: FLD087



Photometric Data


Lumens	9450
LPW	105
Rated Life (Hrs)	50,000
CCT (K)	4000
CRI (Ra)	80
Beam (°)	120

Electrical Data

Input (V) ±10%	220-240
Input (W)	90
LED (W)	90
Input (A)	0.6
Electrical Class	1
Power Factor	0.9
THD (%)	25

Physical Data

Lens Type	Glass
Case Material	Die-Cast Aluminium
Reflector	Aluminium
Dimensions LxWxH (mm)	499 x 100 x 421
Weight (kg)	6.18



1 - Vertical Plane Through Horizontal Angles (0° - 180°) (Through Max. Cd)
2 - Vertical Plane Through Horizontal Angles (90° - 270°)

90W Elite Floodlight, 840



Order Code: FLD087

Accessories

ACS047	Adjustable Sensor Remote Control for Elite Floodlight
--------	---

Product Builder

-SI	INTEGRAL SENSOR (FOR 10W, 20W & 50W VERSIONS)
-----	---

Environmental Data

Max. Ambient (°C)	40
-------------------	----

Min. Ambient (°C)	-25
-------------------	-----

IP Rating	IP65
-----------	------

IK Rating	FLD083-085 IK06 FLD086-090 IK07
-----------	---------------------------------

Warm Up Time	Instant
--------------	---------

General Data

ECA Compliant	Yes
---------------	-----

Energy Rating	A+ (A++ for 10W version)
---------------	--------------------------